SOFT CONNECT
RE-900 Series Support Softwae

Ravel®

Reliability at reach

PRODUCT OVERVIEW

Soft connect is used to monitor the status of RE-900 series panels connected in a network. It can report the fire location and act as early warning for occupants. The software also provides an extensive support for the user to monitor the RE-900 Series Panel with remote notification capability.

FEATURES

- User friendly PC software
- Fire/Fault Identified with location name.
- Zone wise location programming
- Zone wise Isolation Facility
- Events Storage and Printing facilities
- Monitoring the status of Fire Alarm System
- Audible & Visual alerts for Zone wise Fire & fault
- Instant Pop Up's for any Fire or Fault occurence
- Zone wise configurable voice evacuation message for Fire condition
- All functional controls of FACP shall be done through Desktop.
- Two user modes available for security purpose (i.e. USER /ADMINISTRATOR).
- Multiple FACP shall be monitored and controlled from single Desktop
- Shall supports RS-232, LAN & WAN connectivity

SYSTEM REQUIREMENTS:

- OS:- Windows 7 and Above
- Multimedia output is necessary for Voice Annunciation

TOPOLOGY DIAGRAM

1) Via RS 232

RS 232

RE-900 Series

2) Via RE-TCP

Compatible Device

MODEL	DESCRIPTION
RE-900 Series	Fire Alarm Control Panel
RE-900RP Series	Fire Alarm Repeater Panel
RE-TCP	Conventional Ethernet Module

Ordering Information

MODEL	DESCRIPTION
Soft connect-1	Soft connect for RE-900 Series (one to one i.e PC to Panel)
Soft connect-8	Soft connect for RE-900 Series (8 Panels in a network)
Soft connect-16	Soft connect for RE-900 Series (16 Panels in a network)
Soft connect-32	Soft connect for RE-900 Series (32 Panels in a network)