

RE-25SS

Conventional Sounder cum Strobe

Product Overview

RE-25SS sounder cum strobe are designed to simplify installations to provide primary and secondary for fire and security applications. These are ideal where smaller notifications devices is desired. The horns can be flush / ceiling mounted with / without back box. Strobe shall be wired as primary (or) secondary signaling notification appliance flashing at 1Hz over entire voltage operating range. Strobe light consists of Xenon flash tube.

Features:

- Easy to install.
- Operates on 24VDC
- 100db at 30cm.
- Low Current.
- Ceiling / Flush Wall Mount.

Electrical Specification

- Material : FR ABS Plastic
- Input Voltage : 24V DC (15-30V)
- Current : 100 mA @24V
- Relative Humidity : 93 ± 2 @ 32°C
- Operating Temperature : -10 to 50°C
- Sound Level : 88 db +/- 5dB @ 30cm
- Tone Type : 1. Ambulance 2. Police Car 3. Fire engine
- Size : 126(W)*126(H)*55(D)mm



Compatible Device:

Model	Description
RE-717MC	Analogue Addressable Control Module

Ordering Information:

Model	Description
RE-25SS	Sounder cum Strobe

India:

RAVEL ELECTRONICS PVT LTD.,
(An ISO 9001 Certified Company)
150A, Electronics Industrial Estate, Perungudi, Chennai - 96 .India.
E-Mail: marketing@ravelfire.com; Web : www.ravelfire.com

United Kingdom:

RAVEL ELECTRONICS LTD.,
Unit 11, Chancel Industrial Estate, Newhall street,
Willenhall WV13 1NX, West Midlands, United Kingdom.
E-mail: info@ravelfire.co.uk ;Web: www.ravelfire.co.uk