

RE - 125 / RE - 250 PA Amplifier



Features

- Better Sound quality in Digital format.
- 19" 2U rack mountable
- Low power consumption
- Power on, Audio level Indication.
- Class D Amplifier
- Low Heat dissipation.
- Compact size

Specifications

Primary Power	: 220VAC \pm 10%, 50 Hz.
Standby Voltage	: 24 VDC
Maximum DC Current	: 10Amps
audio output	: 100V
Maximum Watts	: 125 / 250 Watt
Audio Input	: from main console
Dimensions(2U)	: (484 W X 88 H X 325D)mm
<u>Operating Condition:</u>	
Operating Temperature	: 0 - 49° C / 32-120° F.
Relative Humidity	: 93 \pm 2% RH (non-condensing) at 32 \pm 2° C / 90 \pm 3° F.

Ordering Information

MODELS	DESCRIPTION
RE - 125	125 W Amplifier
RE - 250	250 W Amplifier

India:

RAVEL ELECTRONICS PVT LTD.,
(An ISO 9001 Certified Company)
150A, Electronics Industrial Estate, Perungudi, Chennai - 96 .India.
E-Mail: marketing@ravelfire.com; Web : www.ravelfire.com

United Kingdom:

RAVEL ELECTRONICS LTD.,
Unit 11, Chancel Industrial Estate, Newhall street,
Willenhall WV13 1NX, West Midlands, United Kingdom.
E-mail: info@ravelfire.co.uk ;Web: www.ravelfire.co.uk